



(43) International Publication Date
12 May 2005 (12.05.2005)

PCT

(10) International Publication Number
WO 2005/042189 A3

- (51) **International Patent Classification⁷:** **B22D 41/18**

(21) **International Application Number:**
PCT/US2004/036718

(22) **International Filing Date:**
3 November 2004 (03.11.2004)

(25) **Filing Language:** English

(26) **Publication Language:** English

(30) **Priority Data:**
60/516,902 3 November 2003 (03.11.2003) US

(71) **Applicant (for all designated States except US):** **VESUVIUS CRUCIBLE COMPANY** [US/US]; 4604 Campells Run Road, Pittsburgh, PA 15205 (US).

(72) **Inventors; and**

(75) **Inventors/Applicants (for US only):** **RICHAUD, Johan L.** [FR/CA]; 6 Waterwheel Cres., Dundas, Ontario L9H-7B6 (CA). **HEASLIP, Lawrence J.** [CA/CA]; 4375 Spruce Avenue, Burlington, Ontario L7L-1L7 (CA). **DORRICOTT, James** [CA/CA]; 2093 Simco Dr., Burlington, Ontario L7M-4E8 (CA).

(74) **Agents:** **SATINA, Donald M.** et al.; Vesuvius USA Corporation, 4604 Campells Run Road, Pittsburgh, PA 15205 (US).

(81) **Designated States (unless otherwise indicated, for every kind of national protection available):** AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) **Designated States (unless otherwise indicated, for every kind of regional protection available):** ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:
— with international search report

Published:
— *with international search report*

[Continued on next page]

- (54) Title: RIPPLED SURFACE STOPPER ROD SYSTEM**



(57) Abstract: The present invention concerns stopper rod system for use in a metallurgical vessel, comprising a stopper rod and a nozzle. At least one of the stopper rod nose (42,56) and the internal surface of the nozzle bore comprise (43,62) a plurality of ripples that are arranged such that the size of a flow channel between the stopper rod nose and the internal stopper rod when the stopper rod system is in an open position discontinuously increases in size as a function of the distance downstream from the point of contact between the stopper rod and the nozzle.



— *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(88) Date of publication of the international search report:

13 October 2005

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
12 May 2005 (12.05.2005)

PCT

(10) International Publication Number
WO 2005/042189 A3

(51) International Patent Classification⁷: **B22D 41/18**

(21) International Application Number:
PCT/US2004/036718

(22) International Filing Date:
3 November 2004 (03.11.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/516,902 3 November 2003 (03.11.2003) US

(71) Applicant (for all designated States except US): **VESUVIUS CRUCIBLE COMPANY** [US/US]; 4604 Campells Run Road, Pittsburgh, PA 15205 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **RICHAUD, Johan L.** [FR/CA]; 6 Waterwheel Cres., Dundas, Ontario L9H-7B6 (CA). **HEASLIP, Lawrence J.** [CA/CA]; 4375 Spruce Avenue, Burlington, Ontario L7L-1L7 (CA). **DORRICOTT, James** [CA/CA]; 2093 Simco Dr., Burlington, Ontario L7M-4E8 (CA).

(74) Agents: **SATINA, Donald M.** et al.; Vesuvius USA Corporation, 4604 Campells Run Road, Pittsburgh, PA 15205 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:


- with international search report
- with amended claims

(88) Date of publication of the international search report:
13 October 2005

Date of publication of the amended claims: 22 December 2005

[Continued on next page]

(54) Title: **RIPPLED SURFACE STOPPER ROD SYSTEM**



(57) Abstract: The present invention concerns stopper rod system for use in a metallurgical vessel, comprising a stopper rod and a nozzle. At least one of the stopper rod nose (42,56) and the internal surface of the nozzle bore comprise (43,62) a plurality of ripples that are arranged such that the size of a flow channel between the stopper rod nose and the internal stopper rod when the stopper rod system is in an open position discontinuously increases in size as a function of the distance downstream from the point of contact between the stopper rod and the nozzle.



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.